

Alliant Energy – Gas Service Manual Table of Contents

Issued: 2023 Supersedes: 2019

| CHAPTER 1 – GENERAL INFORMATION | PAGE |
|--|-------------|
| A. Purpose | 1 |
| B. Codes and Guidelines | 1 |
| C. Disconnection or Refusal of Service | 2 |
| D. Continuity of Service | 2 |
| E. Delivery Pressures | 2 |
| F. Obtaining Gas Service | 4 |
| G. Customer Supplied Volumetric Flow Rate | 5 |
| H. Converting from Another Fuel | 6 |
| I. Customers Increasing Load | 6 |
| J. Relocation of Company Facilities – No Change in Customer Load | 6 |
| K. Gas System Extensions | 7 |
| L. Service Connections | 7 |
| | |



| CHAPTER 2 – COMPANY FACILITIES ON CUSTOMER PREMISES | |
|---|-------------|
| A. General | 1 |
| B. Installation of Company Facilities | 1 |
| C. Access to Company Facilities | 2 |
| D. Corrosion Protection of Company Facilities | 3 |
| E. Automated Meter Reading Requirements | 3 |
| F. Vandalism to Company Facilities | 4 |
| G. Tampering with Company Facilities | 4 |
| | |
| CHAPTER 3 – METERING FACILITY LOCATION AND CLEARANCES | PAGE |
| A. Location and Protection of Company Metering Facilities | 1 |
| B. Gas Meter Set Clearances | 3 |
| | |



| CHAF | TER 4 – GAS METER CONNECTIONS | PAGE |
|------|---|-------------|
| A. | Gas Meter Connections | 1 |
| B. | Concrete Meter Pad | 2 |
| C. | Gas Meter Connection – Type A 0 to 250 Scfh at 7" w.c. or 2 psig delivery pressure | 3 |
| D. | Gas Meter Connection – Type B 251 to 630 Scfh at 7" w.c. or 251 to 1,350 Scfh at 2 psig delivery pressure | 4 |
| E. | Gas Meter Connection – Type C 631 to 1,000 Scfh at 7" w.c. | 5 |
| F. | Gas Meter Connection- Type D 1,001 to 5,000 Scfh at 7" w.c. or 2,301 to 5,000 Scfh at 2 psig delivery pressure | 6 |
| G. | Gas Meter Connection – Type E 1,351 to 2,385 Scfh at 2 psig delivery pressure or 0 to 2,700 Scfh at 5 psig delivery pressure or 0 to 3,400 Scfh at 10 psig delivery pressure or 0 to 3,700 Scfh 15 psig delivery pressure | 7 |
| H. | Gas Meter Connection – Type F 2,701 to 9,300 Scfh at 5 psig delivery pressure or 3,401 to 11,600 Scfh at 10 psig delivery pressure or 3,701 to 14,000 Scfh at 15 psig delivery pressure | 8 |
| I. | Gas Meter Connection – Type G 9,301 to 14,600 Scfh at 5 psig delivery pressure or 11,601 to 18,200 Scfh at 10 psig delivery pressure or 14,001 to 22,200 Scfh at 15 psig delivery pressure | 9 |
| J. | Automated Meter Reading Installations | 10 |



| CHAPTER 5 – CUSTOMER GAS PIPING AND EQUIPMENT | PAGE |
|---|-------------|
| A. General Requirements | 1 |
| B. Customer Gas Piping – Materials | 1 |
| C. Customer Gas Piping – Joining | 4 |
| D. Back Pressure Protection | 5 |
| E. Low-Pressure and Vacuum Protection | 5 |
| F. Overpressure Protection | 6 |
| G. Pressure Testing of Customer Gas Piping | 6 |
| H. Corrosion Protection of Customer Piping Systems | 6 |
| I. Electrical Grounding and Bonding (Non-CSST) | 8 |
| J. Corrugated Stainless Steel Tubing (CSST) Gas Piping | 8 |
| K. Transition to Piping Material Other Than Steel | 10 |
| L. Multiple Meter Installations | 11 |
| M. Odor Fade | 12 |
| CHAPTER 6 – MANUFACTURED HOMES | <u>PAGE</u> |
| A. Scope | 1 |
| B. General | 1 |
| C. Manufactured Home Parks | 2 |
| D. Gas Service to a Single Manufactured Home - Adjacent | 3 |
| E. Gas Service to a Single Manufactured Home - Remote | 3 |
| | |



| APPENDIX | PAGE |
|--|------|
| Approximate Gas Input for Typical Appliances | 1 |
| Customer Piping Material Specifications | 2 |
| Energy Conversion Factors | 3 |